

Features

DC6430 **Dual Directional** Coupler • 15,000 Watts • 80-1000MHz

The Model DC6430 is a dual directional coupler with excellent frequency range and power handling capability. The wide range assures flexibility in coupling high power amplifiers to oscilloscopes, voltmeters, power meters, spectrum analyzers and other measuring instruments. The dual directional design allows the user to monitor both forward and reflected power, a much needed characteristic in RF susceptibility testing for amplifier overdrive protection, field control and load protection. Low insertion loss allows efficient coupling to the load.

The Model DC6430 is uniquely suited for use with our 6000W1000 power amplifier, and other amplifiers operating within this frequency and power range.

The export classification for this equipment is EAR99. These commodities, technology or software are controlled for export in accordance with the U.S. Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

Specifications

FREQUENCY RANGE: 80 MHz-1000 MHz

POWER (Maximum): 15 kW CW

COUPLING FACTOR: 68 dB

COUPLING FLATNESS: ±1.0 dB

DIRECTIVITY: Typical, 20 dB; Minimum, 18 dB

INSERTION LOSS: 0.1 dB maximum

IMPEDANCE (Main Line): 50 ohms, VSWR 1.15:1maximum

CONNECTORS: Main Line, Type EIA fixed/swivel flanges, 3-1/8" Coupled, Type N female

WEIGHT (Maximum): 3.0 kg (6.6 lbs)

SIZE (WxH): 15.2 x 13.2 cm (6.0 x 5.2 in)

EXPORT CLASSIFICATION: EAR99

AR RF/Microwave Instrumentation 160 School House Rd Souderton, PA 18964 215-723-8181

For an applications engineer call:800.933.8181

www.arworld.us

To order AR Products, call 215.723.8181. For an applications engineer call:800.933.8181. Direct to Service call: 215.723.0275 or email: service@arworld.us For Faxing Orders:866.859.0582 (Orders Only Please) info@arworld.us 020117 Approved for public release by AR RF/Microwave Instrumentation

