



DC7445 Dual Directional Coupler

- 3000 Watts
- 6GHz–18GHz

Features

The Model DC7445 is a dual directional coupler with excellent frequency range and power handling capability. The wide range assures flexibility in coupling power amplifiers to receivers, network analyzers, power meters, spectrum analyzers and other measuring instruments. The dual directional design allows the user to monitor both forward and reflected power, a much needed characteristic in RF susceptibility testing for amplifier overdrive protection, field control and load protection. Low insertion loss allows efficient coupling to the load.

The Model DC7445 is intended for use with 250T6G18 and other T Series microwave TWT amplifiers.

The export classification for this equipment is EAR99. These commodities, technology or software are controlled for export in accordance with the U.S. Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

Specifications

FREQUENCY RANGE: 6 GHz–18 GHz

POWER (Maximum): 3 kW CW, 16 kW peak

COUPLING FACTOR: 48 dB \pm 4 dB (includes flatness)

COUPLING FLATNESS: \pm 3 dB

DIRECTIVITY: Typical, 30 dB; Minimum, 20 dB

INSERTION LOSS: 0.3 dB maximum

VSWR (Main Line): 1.3:1 maximum

CONNECTORS:

Main Line, WRD-650
Coupled, Type N female

WEIGHT: 0.64 kg (1.4 lbs)

SIZE (WxH): 2.9 x 3.5 x 30.5 cm (1.13 x 1.4 x 12 in)

EXPORT CLASSIFICATION: EAR99

AR RF/Microwave
Instrumentation
160 School House Rd
Souderton, PA 18964
215-723-8181

For an applications engineer call: 800.933.8181

www.arworld.us

To order AR Products, call 215.723.8181. For an applications engineer call: 800.933.8181. Direct to Service call: 215.723.0275 or email: service@arworld.us For Faxing Orders: 866.859.0582 (Orders Only Please) info@arworld.us
Approved for public release by AR RF/Microwave Instrumentation

081418