

CONDUCTED SUSCEPTIBILITY

# Military & Aerospace Testing





This document has been optimized for electronic media



Smart navigation through technical specifications. Click the green links.



WHEN GETTING RESULTS MATTERS

## THERE IS ONLY ONE CHOICE

Military and avionic testing is all about quality and precision. MIL-MG3 brilliantly fulfills these requirements.


A flexible solution that includes:

- › MIL-STD-461C CS06 spikes, power leads
- › MIL-STD-461 CS106 transients, power leads
- › MIL-STD-461 CS115 bulk cable injection
- › MIL-STD-461 CS116 damped sinusoidal transients
- › MIL-STD-1275 Imported spikes
- › DO-160 section 17 Voltage spikes
- › DO-160 section 19 Inductive switching transients

Ease of use, predefined test routines and large aperture couplers make MIL-MG3 the most efficient and technically advanced instrument in this category.

# FLEXIBLE SOLUTION

MIL-MG3 modular test system is the first of its kind to employ touch screen technology. An enhanced user interface and choice of couplers allow easy expansion to a test suite for MIL-STD and DO-160 impulse requirements



## MIL-MG3 TEST SYSTEM

- MIL-MG3 Mainframe Unit

### Available Plug-Ins

- MIL3-REC (CS115)
- MIL3-10K10M (CS116)
- MIL3-30M100M (CS116)
- MIL3-CS116 CUSTOM FREQUENCY
- MIL3-SPIKE (CS106, CS06)
- MIL3-SPIKE-SLOW (CS06)
- MIL3-SPIKE-FAST (CS06)
- MIL3-1275
- MIL3-DO-160 S17
- MIL3-DO-160 S19

## Accessories for MIL-STD-461

- **CN-BT6**  
Only one coupler for CS115 and CS116 testing. No change of EUT cables position. Aperture diameter (50mm)
- **VERI-MIL3**  
Includes all necessary calibration and measurement loads.

## Included Benefits

<b>Stable</b>	Pulse reproducibility during test cycle
<b>Precise</b>	Repeatable test results over long time
<b>Reliable</b>	Evolution of established technology
<b>Fast</b>	Minimum setup and calibration time
<b>Polarity</b>	Maintain test integrity by electronic switching
<b>Automated</b>	Save and repeat test routines

# AVAILABLE PLUG-INS

Modules are available for MIL-MG3 system to cover the CS115, CS116, CS106, CS06, DO-160 section 17 and 19 test requirements. Select modules for specific test and later add new modules to enhance the system capability. New modules are automatically recognised and controlled by the system firmware.



## MIL3-REC

MIL-STD-461 / CS115

- › Bulk cable injection impulse
- › Rise & fall time < 2ns pulse duration 30ns



## MIL3-10K10M

MIL-STD-461 / CS116

- › Damped sinusoidal transients
- › Oscillation frequencies 10kHz, 100kHz, 1MHz, 10MHz.



## MIL3-30M100M

MIL-STD-461 / CS116

- › Damped sinusoidal transient
- › Oscillation frequencies 30MHz, 100MHz.



## MIL3-CS116 CUSTOM FREQUENCY

MIL-STD-461 / CS116

- › Choose any CS116 frequency in the range 10kHz to 30MHz



## MIL3-SPIKE

MIL-STD-461 / CS106

- › Transients, power leads
- › Rise time 1.5us and pulse duration 5us



## MIL3-SPIKE -SLOW & FAST

MIL-STD-461C / CS06

- › Spikes, power leads
- › Pulse duration 10us and 0.15us



## MIL3-1275

MIL-STD-1275

- › Imported spike
- › Oscillation frequency 100kHz



## MIL3-DO-160-S17

DO-160 SECTION 17

- › Voltage spikes
- › Rise time 2us and pulse duration 10us



## MIL3-DO-160-S19

DO-160 SECTION 19

- › Inductive switching transients
- › Burst duration > 150us and spike frequency 250kHz



#### Enhanced safety is standard

Red/Yellow Emergency Stop button on front panel of generator can be complemented with remote option.

Add warning lamps and a test cabinet for enhanced test place safety.

## UNIQUE FEATURES

Leading technology - New designs take advantage of latest innovations.

Latest generation, solid state, precise technology

### Fast and stable



No generator or coupler adjustments required. System is ready for calibration or testing in less than 30 seconds.

### Test reporting



Generate test reports via USB interface or built in webserver as csv, html and pdf formats.

### Always up to date




Firmware download from internet directly into the instrument.

### Extend testing capability



Modular, on site upgradeable system based on plugin technology.



## EPOS – TOUCH THE FUTURE

EMC PARTNER Operating System (EPOS) is an independent software with free-of-charge updates for lifetime. EPOS is based on a full colour graphic interface and easy to follow on-screen graphics. Pop-up help gives information when needed, directly during the setting process. EPOS is full of features found only in top of the range instrumentation.

### Integrated Web Server



Use any browser to access test reports from the generator.

### Simple touch screen navigation



Save time with the latest in intuitive menu structures.

### Interactive Interface



User interface adapted to specific modules.

### We speak your language



Select between English, German, French, Italian, Spanish, Russian, Chinese (traditional and simplified).






## TEMA3000 SOFTWARE SUITE


The best solution for professional EMC Test Labs enables comfortable test setups, easy parameter changes and customizable test reports and DSO integration.

### Customizable test reports



- › Customize & edit your protocols
- › Export to multiple file formats
- › Integrate DSO measurements

### Manage tests and sequences



- › Predefined test setups
- › Save and load own tests and sequences

### Productive workflow



- › Minimum learning time
- › Integrated assistant function

### Smart connectivity



- › Transfer tests / reports to PC
- › Remote control from computer



# Technical Specifications

## PLUGINS

MIL-MG3	Main frame	MIL3-REC	MIL3-10K10M	MIL3-30M100M	MIL3-CS116 CUSTOM	MIL3-SPIKE	MIL3-SPIKE-SLOW	MIL3-SPIKE-FAST	MIL3-DO-160-S17	MIL3-DO-160-S19	MIL3-1275B
MIL-461G CS115	✓	✓									
MIL-461G CS116	✓		✓	✓	✓						
MIL-461C CS06	✓					✓	✓	✓			
MIL-461F CS106	✓					✓					
MIL-1275B	✓										✓
DO-160 S17	✓								✓		
DO-160 S19	✓									✓	
ECSS-E-ST-20-07C rev1.							✓	✓			

## ACCESSORIES

MIL-MG3	Main frame	MIL3-REC	MIL3-10K10M	MIL3-30M100M	MIL3-CS116 CUSTOM	MIL3-SPIKE	MIL3-SPIKE-SLOW	MIL3-SPIKE-FAST	MIL3-DO-160-S17	MIL3-DO-160-S19	MIL3-1275B
CN-BT6	✓	✓	✓	✓	✓						
VERI-MIL3	✓	✓	✓	✓	✓						
CN-MIG-BT5	✓					✓	✓		✓		
DC-S17CL	✓					✓	✓	✓	✓		
VERI5	✓					✓	✓	✓			
SHUNT0E1	✓						✓				
VERI01 OSI	✓							✓			
VERI50	✓								✓		
20dB ATTN.	✓		opt								
I-PROBE-CS	✓	✓	✓	✓	✓						
TEMA3000	✓	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt

# 1. MIL-MG3 MAINFRAME AND PLUGINS

## 1.1. TECHNICAL SPECIFICATIONS

### MIL-MG3 Mainframe

<b>Operating system</b>	EPOS proprietary firmware
<b>Languages</b>	8 menu languages, selectable
<b>User interface</b>	7" capacitive touch display
<b>Connectivity</b>	gigabit ethernet, USB, RS485
<b>Synchronization on signals</b>	40 – 800 Hz
<b>Synchronization source</b>	external, 50 – 280 V
<b>Synchronization angle</b>	0 – 359° ± 5°, 1° step
<b>Impulse polarity</b>	positive, negative, electronic switching
<b>Automatic ramp</b>	test level
<b>Trigger out</b>	BNC, max. 6 V
<b>Programmable connectors</b>	6 BNC connectors (inputs/outputs) as follows
<b>Programmable input functions</b>	Trigger input, Start Test, Stop Test, EUT Fail, EUT Mark, Emergency Stop
<b>Programmable input max. voltage</b>	low range: 0 – 1.5 V, high range: 2.3 – 24 V
<b>Programmable output functions</b>	Running State, Safety Circuit State
<b>Programmable output max. U, I</b>	max. 24 V, max. 300 mA
<b>Safety features (standard)</b>	Emergency stop button on front panel red/yellow as per IEC 60947-5-5, IEC 60204-1, ISO 13850 Safety circuit
<b>Safety accessories (optional)</b>	WARNING LAMP (24 V, max. 2.4 W), TC-ST test cabinet Remote EMERGENCY STOP button



### MIL3-REC

<b>Standard</b>	MIL-STD-461, CS115
<b>Test level into 100 Ω</b>	1 – 10 A ± 10 % , adjustable
<b>Waveform</b>	rectangular pulse
<b>Z<sub>out</sub></b>	50 Ω
<b>Pulse rise and fall time</b>	< 2 ns
<b>Pulse duration</b>	≥ 30 ns
<b>Repetition rate</b>	max. 33 Hz
<b>Requires</b>	CN-BT6, VERI-MIL3
<b>Optional</b>	I-PROBE-CS



### MIL3-10K10M

<b>Standard</b>	MIL-STD-461, CS116 (10 kHz – 10 MHz)
<b>Test level into 100 Ω</b>	@ 10 kHz: 0.02 – 0.22 A ± 10 %, adjustable
<b>Test level into 100 Ω</b>	@ 100 kHz: 0.2 – 2.0 A ± 10 %, adjustable
<b>Test level into 100 Ω</b>	@ 1 MHz: 1 – 12 A ± 10 %, adjustable
<b>Test level into 100 Ω</b>	@ 10 MHz: 2 – 12 A ± 10 %, adjustable
<b>Waveform</b>	damped oscillation@10k,100k,1MHz,10MHz ±10%
<b>Z<sub>out</sub></b>	≤ 100 Ω
<b>Damping factor (Q)</b>	15 ± 5 for all frequencies
<b>Repetition rate</b>	max. 2 Hz for all frequencies
<b>Coupler for all frequencies</b>	CN-BT6
<b>Calibration fixture all freq.</b>	VERI-MIL3
<b>Optional</b>	I-PROBE-CS, 20dB ATTENUATOR



### MIL3-30M100M

<b>Standard</b>	MIL-STD-461, CS116 (30 MHz – 100 MHz)
<b>Test level into 100 Ω</b>	@ 30 MHz: 2 – 12 A ± 10 %, adjustable
<b>Test level into 100 Ω</b>	@ 100 MHz: 1 – 6 A ± 10 %, adjustable
<b>Waveform</b>	damped oscillation@30MHz,100MHz ±10%
<b>Z<sub>out</sub></b>	≤ 100 Ω
<b>Damping factor (Q)</b>	15 ± 5 for all frequencies
<b>Repetition rate</b>	max. 2 Hz for all frequencies
<b>Coupler for all frequencies</b>	CN-BT6
<b>Calibration fixture all freq.</b>	VERI-MIL3
<b>Optional</b>	I-PROBE-CS



### MIL3-CS116 CUSTOM FREQUENCY

<b>Standard</b>	MIL-STD-461, CS116
<b>Test level into 100 Ω</b>	according to Fig. CS116-2
<b>Frequency</b>	choose any frequency from 10 kHz to 30 MHz
<b>Waveform</b>	damped oscillation
<b>Z<sub>out</sub></b>	≤ 100 Ω
<b>Damping factor (Q)</b>	15 ± 5 for all frequencies
<b>Repetition rate</b>	max. 2 Hz for all frequencies
<b>Coupler for all frequencies</b>	CN-BT6
<b>Calibration fixture all freq.</b>	VERI-MIL3
<b>Optional</b>	I-PROBE-CS



### MIL3-SPIKE

<b>Standard</b>	MIL-STD-461F CS106, MIL-STD-461C CS06
<b>Output impedance</b>	< 2 $\Omega$
<b>Test level into 5 <math>\Omega</math></b>	100 – 600 V $\pm$ 10 %, adjustable
<b>Waveform</b>	voltage spike
<b>Pulse rise time</b>	1.5 $\mu$ s $\pm$ 0.5 $\mu$ s
<b>Pulse front time</b>	3.5 $\mu$ s $\pm$ 0.5 $\mu$ s
<b>Pulse duration</b>	5 $\mu$ s $\pm$ 22 %
<b>Voltage sag amplitude</b>	$\leq$ 120 V @ 400 V test level
<b>Voltage sag duration</b>	$\leq$ 20 $\mu$ s @ 400 V test level
<b>Repetition rate</b>	max. 10 Hz
<b>Synchronization</b>	0 – 359° $\pm$ 5°, 1° step
<b>Requires</b>	CN-MIG-BT5, VERI5, DC-S17CL



### MIL3-SPIKE-SLOW

<b>Standard</b>	MIL-STD-461C CS06, ECSS-E-ST-20-07C Rev. 1 CS, power leads, transients
<b>Waveform duration</b>	10 $\mu$ s $\pm$ 20 %
<b>Polarity</b>	positive and negative
<b>Repetition rate</b>	0.1 – 60 s
<b>Synchronization</b>	0 – 359° $\pm$ 5°
<b>Synchronization input</b>	50 – 280 V, 40 – 800 Hz
<b>Serial injection</b>	
<b>Test level</b>	20 – 300 V $\pm$ 10 %
<b>Z<sub>out</sub></b>	< 2 $\Omega$
<b>EUT current serial inj.</b>	max. 1280A @50Hz, 160A @400Hz, 80A @800Hz
<b>Requires</b>	CN-MIG-BT5, VERI5
<b>Optional</b>	DC-S17CL (see EUT supply limits)
<b>Parallel injection</b>	
<b>Test level</b>	20 – 500 V $\pm$ 10 %
<b>Z<sub>out</sub></b>	< 1 $\Omega$
<b>EUT voltage parallel inj.</b>	max. 250V @DC - 60Hz, 60V @60 - 400Hz, 30V @400 - 800Hz
<b>Requires</b>	VERI5, SHUNT0E1
<b>Optional</b>	DC-S17CL (see EUT supply limits)



### MIL3-SPIKE-FAST

<b>Standard</b>	MIL-STD-461C CS06, ECSS-E-ST-20-07C Rev. 1 CS, power leads, transients
<b>Waveform duration</b>	0.15 $\mu$ s $\pm$ 20%
<b>Polarity</b>	positive and negative
<b>Repetition rate</b>	0.1 – 60 s
<b>Synchronization</b>	0 – 359° $\pm$ 5° up to 400 Hz
<b>Synchronization input</b>	50 – 280 V, 40 – 800 Hz



#### Serial injection

<b>Test level</b>	20 – 400 V $\pm$ 10 %
<b>Z<sub>out</sub></b>	< 5 $\Omega$ @ standard test level
<b>EUT current serial inj.</b>	max. 32 A @ DC – 800 Hz
<b>Requires</b>	<a href="#">VERI5</a>
<b>Optional</b>	<a href="#">DC-S17CL</a> (see EUT supply limits)

#### Parallel injection

<b>Test level</b>	20 – 400 V $\pm$ 10 %
<b>Z<sub>out</sub></b>	< 5 $\Omega$ @ standard test level
<b>EUT voltage parallel inj.</b>	max. 250 V @ DC – 800 Hz
<b>Requires</b>	<a href="#">VERI5</a> , <a href="#">VERI01 OSI</a>
<b>Optional</b>	<a href="#">DC-S17CL</a> (see EUT supply limits)

### MIL3-DO-160-S17

<b>Standard</b>	DO-160 Section 17
<b>Output impedance</b>	50 $\Omega$ $\pm$ 10 %
<b>Test level OC</b>	50 – 1200 V $\pm$ 10 % , adjustable
<b>Waveform</b>	voltage spike
<b>Pulse rise time</b>	1 – 2 $\mu$ s $\pm$ 30 %
<b>Pulse duration</b>	> 10 $\mu$ s
<b>Repetition rate</b>	max. 2 Hz
<b>Synchronization</b>	0 – 359° $\pm$ 5°, 1° step input 50 - 250 V / 40 - 800 Hz
<b>EUT supply</b>	250 V / DC - 60 Hz
<b>parallel injection</b>	60 V / 60 - 400Hz 30 V / 400 - 800Hz current limited only by decoupling
<b>Requires</b>	<a href="#">CN-MIG-BT5</a> , <a href="#">VERI50</a> , <a href="#">DC-S17CL</a>



### MIL3-DO-160-S19

<b>Standard</b>	DO-160 Section 19 – fig. 19-6, inductive switch- ing transient
<b>Resistance</b>	175 $\Omega$ $\pm$ 10 %
<b>Inductance</b>	1.5 H $\pm$ 10 %
<b>Test level</b>	$\geq$ 600 V






<b>Waveform</b>	voltage spikes/burst
<b>Spike repetition period</b>	in the range 0.2 – 10 $\mu$ s
<b>Burst total duration</b>	in the range 50 - 1000 $\mu$ s
<b>Event repetition</b>	0.1 – 60 s, adjustable
<b>Test duration</b>	1 – 65535 s
<b>Included</b>	cables for coupling 0.5 m, 1.0 m, 2.0 m

### MIL3-1275B

<b>Standard</b>	MIL-STD-1275B, figure 10 MIL-STD-1275E, sec 5.3.3.1.1
<b>Test level</b>	100 – 1000 V $\pm$ 10 %, in open circuit
<b>Waveform</b>	ring wave
<b>Rise time 10 – 90 %</b>	< 50 ns
<b>Oscillation frequency</b>	100 – 500 kHz
<b>Pulse repetition</b>	max. 2 Hz
<b>Max. EUT power</b>	
<b>DC</b>	28 V / 30 A
<b>AC</b>	230 V / 10 A or 115 V / 25 A @ 50/60 Hz



## 1.2. POWER, CLIMATIC CONDITIONS, SHIPPING WEIGHT, DIMENSIONS

### MIL-MG3 mainframe

<b>Mains adapter</b>	100 – 240 V $\pm$ 10 % (50/60 Hz)
<b>Power consumption</b>	ON < 150 VA, standby < 15 VA
<b>Temperature range</b>	10 – 35 °C
<b>Humidity</b>	< 80 % non-condensing
<b>Air pressure</b>	86 – 106 kPa
<b>Mainframe weight</b>	17 kg
<b>W x d x h</b>	45 x 57 x 19 cm
<b>Version</b>	19" unit, 4 UH
<b>Included articles</b>	
<b>Power cord</b>	with country plug
<b>User manual</b>	with conformity declaration
<b>Calibration certificate</b>	factory calibration for each plugin ordered
<b>Ethernet cable</b>	1 piece

## 2. ACCESSORIES FOR MIL-MG3

### 2.1. TECHNICAL SPECIFICATIONS

#### CN-BT6

<b>Standard</b>	MIL-STD-461 CS115 and CS116
<b>Application</b>	injection probe
<b>Frequency range CS115</b>	usable rise time from 1 ns
<b>Frequency range CS116</b>	10 kHz – 100 MHz
<b>EUT supply</b>	max. 150A@50/60Hz, 20A@400Hz, 10A@800Hz
<b>Aperture</b>	5 cm diameter
<b>Dimensions l x h x w</b>	25 x 17 x 15 cm
<b>Weight</b>	5 kg
<b>Included</b>	50 Ω termination, 1 m cable, 2 m cable
<b>Requires</b>	CS115 and/or CS116 modules, VERI-MIL3



#### VERI-MIL3

<b>Application</b>	calibration fixture for CN-BT6 (CS115, CS116)
<b>Weight</b>	4.5 kg
<b>Dimensions l x h x w</b>	34 x 13 x 15 cm
<b>Included</b>	2 x 20 dB N-type, 2 x 20 dB BNC, 1 m cable



#### CN-MIG-BT5

<b>Standards</b>	MIL-STD-461F CS106, MIL-STD-461C CS06, DO-160 Section 17 serial injection
<b>Application</b>	injection probe
<b>Frequency range</b>	10 kHz – 10 MHz
<b>EUT supply</b>	CS106: max. 150A@50/60Hz, 20A@400Hz, 10A@800Hz CS06 SLOW: max. max. 1280A @50Hz, 160A @400Hz, 80A @800Hz Section 17, serial injection: max. 1000A@50/60Hz, 160A@400Hz, 80A@800Hz
<b>Aperture</b>	8 x 7 cm
<b>Dimensions l x h x w</b>	22 x 22 x 20 cm
<b>Weight</b>	13 kg
<b>Included</b>	1 m cable, 1 turn calibration loop
<b>Requires</b>	CS106 or CS06 modules or S17 module, DC-S17CL



#### DC-S17CL

<b>Standards</b>	MIL-STD-461F CS106, MIL-STD-461C CS06 DO-160 Section 17
<b>Application</b>	decoupling units for power supply side
<b>For serial injection</b>	4 x decoupling capacitors, in 2 boxes
<b>Decoupling capacitance</b>	10 μF
<b>EUT voltage</b>	max. 250V, DC - 800Hz
<b>EUT current</b>	not limited by decoupling capacitors



<b>For parallel injection</b>	2 x decoupling inductors
<b>Decoupling inductance</b>	1.8 mH
<b>EUT voltage</b>	max. 250V, DC - 800Hz
<b>EUT current</b>	max. 16 A
<b>Weight</b>	7 kg, all 4 modules and acc. in carrying case
<b>Dimensions</b>	34 x 28 x 17 cm (carrying case)
<b>Included</b>	connection cables, carrying case

### SHUNTOE1

<b>Application</b>	calibration of WF2, WF3 short circuit current
<b>Impedance</b>	0.1 $\Omega$ $\pm$ 2 %
<b>Output</b>	100 mV/A
<b>Maximum setting AVI-LV3</b>	WF2: 1600 V, WF3: 1900 V
<b>Weight</b>	0.15 kg
<b>Dimensions</b>	12 x 2.5 x 2.5 cm
<b>Requires</b>	MIL-MG3, MIL-SPIKE-SLOW



### VERI01 OSI

<b>Application</b>	0.1 $\Omega$ shunt for 3, 10, 30 MHz DOW SC current
<b>Input impedance</b>	0.1 $\Omega$ $\pm$ 2 %
<b>Input voltage</b>	max. 6.3 kV
<b>3 dB bandwidth</b>	> 400 MHz
<b>Power dissipation</b>	max. 3 W, max. 1000 spikes/s @ 4.4 kV
<b>Measurement ratio</b>	1 V @ 10 A in 1 M $\Omega$ $\pm$ 2 %
<b>Dimensions</b>	8.5 x 2.5 x 2.5 cm
<b>Weight</b>	0.1 kg
<b>Requires</b>	MIL-MG3, MIL-SPIKE-FAST



### VERI5

<b>Standard</b>	MIL-STD-461F CS106, MIL-STD-461C CS06
<b>Application</b>	non-inductive calibration load
<b>Input impedance</b>	5 $\Omega$ $\pm$ 2 %
<b>Power dissipation</b>	max. 10 W
<b>Voltage</b>	max. 500 V as per CS106
<b>Transfer ratio</b>	DSO 1M $\Omega$ : 1:50 (34dB); DSO 50 $\Omega$ : 1:100 (40dB)
<b>Weight</b>	0.2 kg
<b>Dimensions</b>	12 x 2.5 x 2.5 cm
<b>Included</b>	factory calibration report



## VERI50

<b>Standard</b>	DO-160 Section 17
<b>Application</b>	non-inductive calibration load
<b>Input impedance</b>	50 Ω ± 2 %
<b>Power dissipation</b>	max. 10W
<b>Voltage</b>	max. 1200 V as per Section 17
<b>Transfer ratio</b>	DSO 1MΩ: 1:50 (34dB); DSO 50 Ω: 1:100 (40dB)
<b>Weight</b>	0.2 kg
<b>Dimensions</b>	12 x 2.5 x 2.5 cm
<b>Included</b>	factory calibration report



## 20dB ATTENUATOR (optional)

<b>Application</b>	att. reducing test level with MIL3-10K10M
<b>Level with 20 dB (10 kHz)</b>	for ex: 22 mA @ gen. setting 220 mA
<b>Weight</b>	0.1 kg
<b>Dimensions</b>	11 x 2.5 x 2.5 cm
<b>Included</b>	factory calibration report



## I-PROBE-CS

<b>Standards</b>	MIL-STD-461G: CS115, CS116
<b>Application</b>	current probe for test level and rise time meas.
<b>Output connector</b>	N (adapter for BNC optional, ask sales)
<b>Frequency range</b>	10 kHz – 400 MHz
<b>Usable rise time</b>	1 ns
<b>Aperture</b>	50.8 mm (excellent for CN-BT6)
<b>Input level</b>	max. 4 A r.m.s., 15 A peak
<b>Transfer impedance</b>	- 6 dBΩ
<b>Current time product</b>	max. 0.6 mAs
<b>Weight</b>	1 kg
<b>Dimensions</b>	14.7 x 12.7 x 3.2 cm
<b>Included</b>	carrying case

## TEMA3000

<b>Application</b>	modular control software for MIL-MG3 system
<b>License</b>	1 license for 1 generator
<b>TEMA3000 basic</b>	remote control of generator, single tests
<b>TEMA3000-SEQUENCE</b>	more single tests linked in a sequence
<b>TEMA3000-REPORT</b>	generation of customized test reports
<b>TEMA3000-DSO</b>	control of DSOs via Ethernet, data in report
<b>TEMA3000-LIBRARY</b>	collection of norm pre-programmed tests
<b>Compatibility</b>	Windows XP, 7, 8, 10
<b>For generators</b>	MIL-MG3, AVI-LV3, IMU Series, other



# THE EMC PARTNER PRODUCT RANGE

Find further brochures on our website [emc-partner.com/brochures](http://emc-partner.com/brochures) or contact your local representative for a hardcopy.


## IMMUNITY TESTS

Transient Test Systems for all EMC tests on electronic equipment. ESD, EFT, surge, AC dips, AC magnetic field, surge magnetic field, common mode, damped oscillatory and DC dips. According to IEC and EN 61000-4-2, -4, -5, -8, -9, -10, -11, -12, -13, -14, -16, -18, -19, -29.



## LIGHTNING TESTS

Impulse test equipment and accessories for aircraft, military and telecom applications. Complete solutions for RTCA / DO-160 and EUROCAE / ED-14 for indirect lightning on aircraft systems, MIL-STD-461 tests CS106, CS115, CS116, CS117, CS118 and Telecom, ITU-T K.44 for impulse, power contact and power induction.



## COMPONENT TESTS

Impulse generators for testing varistors, gas discharge tubes (GDT), surge protective devices (SPDs), X / Y capacitors, circuit breakers, electricity meters, protection relays, insulation material, suppressor diodes, connectors, chokes, fuses, resistors, emc-gaskets, cables, etc.




## SYSTEM AUTOMATION

A full range of accessories enhance the test systems. Test cabinets, test pistols, adapters and remote control software, simplify interfacing with the EUT. Programmable power supply unit, EMC hardened for frequencies from 16.7Hz to 400Hz. PS3-SOFT-EXT complies with IEC / EN 61000-4-14 and -4-28.



## SERVICE

Our commitment starts with a quality management system backing up our ISO 17025 accreditation. With the SCS number 146, EMC PARTNER provide accredited calibration and repairs. Our customer support team is at your service!



For further information please do not hesitate to contact your local EMC PARTNER AG representative.  
Visit our website for more information and contact details.

# [www.emc-partner.com](http://www.emc-partner.com)



## Swiss Headquarters

EMC PARTNER AG  
Baselstrasse 160  
CH - 4242 Laufen

Phone +41 61 775 20 30  
Fax +41 61 775 20 59  
Email [service@emc-partner.ch](mailto:service@emc-partner.ch)  
Web [www.emc-partner.com](http://www.emc-partner.com)

## Your local representative

Information and specifications in this document are an indication of capability only. Version 6.0. Subject to change without notice. EMC PARTNER AG publishes only the English version of this document. Translation into other languages is not guaranteed to be a true representation of content or specification.

© by EMC PARTNER AG. No changes or reproduction without permission of EMC PARTNER AG allowed.