



04E PROBE

Electric Field Probe: E Field, 3 MHz ÷ 40 GHz

Key Features:

- Frequency range: 3 MHz ÷ 40 GHz
- Dynamic Range: > 56 dB
- Directivity: Isotropic

Compatibility:

- NHT310 and NHT3D meters

Typical Application:

- Industrial ovens, welding systems, RF heating, tempering and drying systems
- Diathermy equipment and medical devices RF generators, NMR machines
- Power plants and related maintenance and control systems
- Sensitive site (hospital)
- Measurement systems for railway and round transport
- Wireless telecommunication systems such as mobile phone base stations, satellite communication equipment, Broadcasting equipment, Wi-Fi, Wi-Max and LTE



Information subject to change without prior notice

MICRAD

Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 /Fax. +39 0763 394423 info@microrad.it - www.microrad.it



04E PROBE

Electric Field Probe: E Field, 3 MHz ÷ 40 GHz

Description:

The 04E probe is based on a set of three mutually orthogonal diode dipoles. The signal from the three dipoles is used by the NHT310 or NHT3D instruments to calculate the isotropic value of the field.

The 04E probe is able to detect both CW (Continuous Wave) and modulated signals in the frequency ranges from 3MHz to 40GHz, allowing operators to cover applications in the industrial, scientific, medical, telecommunications and power plants sectors.

The high sensitivity of this probe makes it ideal for protectionist measurement of human exposure to electric fields in both public and professional environments.

The introduction of the signal envelope sampling technique, carried out with the NHT3D meter, allows not only a reliable reading of the field value, but also, for the first time, the graphical representation in the time domain of the form factor of the analyzed signal. This innovative technique opens up new analytical perspectives, allowing to distinguish and evaluate intermittent or pulse signals with important crest factors such as those typical of mobile telephones or radar.

TECHNICAL SPECIFICATIONS	
Frequency range	3 MHz ÷ 40 GHz
Type of frequency response	Flat
Measurement range	0.5 ÷ 350 V/m (cw)
Dynamic range	56 dB
Sensor type	Diode dipoles
Directivity	Isotropic
Frequency response (typical)	± 2 dB (10 MHz ÷ 7 GHz)
	± 6 dB (7 GHz ÷ 40 GHz)
Linearity	± 0.5 dB (2 ÷ 350 V/m)
Isotropic response	± 0.4 dB (@ 100 MHz)
	± 0.5 dB (@ 1 GHz)

GENERAL CHARACTERISTICS	
Recommended calibration interval	24 months
Operation temperature	0°C ÷ 50°C
Size	327 x 60 Ø(mm)
Weight	120g
Country of origin	Italy

Information subject to change without prior notice



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
 Tel. +39 0763 393291 /Fax. +39 0763 394423 info@microrad.it - www.microrad.it